


RYCO FILTERS



FITTING INSTRUCTIONS FOR RYCO CABIN FILTER RCA218C.

SABB 9-5

(Filter is located behind glove box)



1. The cabin air filter is located behind the glovebox in the passenger side.
2. The glove box unit has to be removed to access the cabin air filter housing. Please follow the steps carefully or refer to the owners manual if unsure.
3. Start by unclipping the lower carpet trim attached to the side of the centre console. Pull the carpet trim forward and proceed to remove the screws holding the upper plastic trim right below the glove box unit in the footwell, carefully pull them and disconnect light connector before removing it completely.
4. Remove the three screws holding the bottom section of the glove box. Open the glove box and remove the two screws holding each side then remove the top three screws, close the glove box and gently pull out and disconnect all hoses and connectors to be able to fully remove the glove box.
5. Remove the seven bolts holding the cabin air filter housing lid and remove it. Slide the old cabin filter out carefully to avoid accumulated debris spreading around. Clean the area and insert the new filter making sure it is in the right air flow direction. Refit all components in reverse order.

GUD Automotive Pty Ltd
29 Taras Ave Altona North
Victoria 3025 Australia.
www.rycofilters.com.au

GUD Automotive -
A division of GUD (NZ) Holdings Limited
626A Rosebank Road Avondale
Auckland, New Zealand
www.ryco.co.nz